

# Pactrade Marine

2011 & 2012 CATALOG



Marine & RV LED lighting, switch panels,  
solar ventilators and other accessories.

# About us

***Pactrade Marine is a manufacturer and importer headquartered in Edmond, Oklahoma. Pactrade Marine specializes in marine and RV lighting, switches and accessories. Our company is constantly investing in designing new and innovative LED lighting fixtures, solar ventilator units and switch panels.***

***Besides offering products of the highest quality, our focus on customer service is what sets us apart. We support our customers with inventory, sales and warranty coverage. Our dedicated customer service department are trained to give you excellent and superior service.***

***Sincerely  
Pactrade Marine Family***

**Pactrade Marine  
1200 S. Fretz Ave  
Edmond OK 73003**


**Tel: 405-216-0403**

**Fax: 405-216-9273**

**E-mail: [info@pactrademarine.com](mailto:info@pactrademarine.com)**

**Website: [www.pactrademarine.com](http://www.pactrademarine.com)**

# LED Swivel Reading & Wall Light




**Dimmable LED Wall Reading Light**

*Small, bright and flexible LED reading light in polished brass housing and frosted glass shade. Exquisite and innovative design is ideal for any interior wall lighting. Light comes with a toggle ON/OFF switch. Base Dia. 52mm x 110mm H*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass/  
**Frosted Glass**  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **Material**  
**P00005-BLW** **Lacquered Brass**




**Dimmable LED Wall Reading Light**

*Small, bright and flexible LED reading light in polished brass housing and frosted glass shade. Exquisite and innovative design is ideal for any interior wall lighting. Light comes with a toggle ON/OFF switch. Light is dimmable. Base Dia. 54mm x 101.8mm H*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass /  
**Frosted Glass**  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **Material**  
**P00006-BLW** **Lacquered Brass**




**Dimmable LED Wall Reading Light**

*Small, bright and flexible LED reading light in polished brass housing and frosted glass shade. Exquisite and innovative design is ideal for any interior wall lighting. Light comes with a toggle ON/OFF switch. Light is dimmable. Base Dia. 54mm x 105.8mm H*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass/  
**Frosted Glass**  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **Material**  
**P00009-BLW** **Lacquered Brass**




**Dimmable LED Swivel Reading/Wall Light**

*Small, bright and flexible LED Swivel Reading Light with frosted white glass shade. Light comes with ON/OFF toggle switch. Elegant and innovative design for any reading light applications. Light can be adjusted to shine upwards for wall lighting application. Light is dimmable. Base Dia. 54mm x 105mm H*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass /  
**Frosted Glass**  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **Material**  
**P00008-BLW** **Lacquered Brass**



**Dimmable LED Swivel Reading/Wall Light**


*Small, bright and flexible LED Swivel Reading Light with frosted white glass shade. Light comes with ON/OFF toggle switch. Elegant and innovative design for any reading light applications. Light can be adjusted to shine upwards for wall lighting application. Light is dimmable. Base Dia. 54mm x 105mm H*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass/  
**Frosted Glass**  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **Material**  
**P00007-BLW** **Lacquered Brass**



# LED Swivel Reading Light




## LED Swivel Reading Light

*Small, bright and flexible LED reading light in polished brass lacquered housing. Exquisite and innovative design is ideal for any interior lighting applications.*

*Base Dia. 40mm, Lens housing Dia. 30mm and Swivel length 28 mm*

**Material:** Brass  
**Housing Color:** Polished Lacquered Brass  
**LED Quantity:** 1 x 1W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V  
**Wattage:** 1.2W  
**Lumen:** 70-80  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00001-BLW  
**Material** Lacquered Brass




## LED Swivel Reading Light

*Small, bright and flexible LED reading light in polished brass lacquered housing. Exquisite and innovative design is ideal for any interior lighting applications.*

*Base Dia. 40mm, Lens housing Dia. 30mm and Swivel length 28 mm*

**Material:** Brass  
**Housing Color:** Polished Lacquered Brass  
**LED Quantity:** 1 x 1W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 1.2W  
**Lumen:** 70-80  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00002-BLW  
**Material** Lacquered Brass




## LED Swivel Reading Light

*Small, bright and flexible LED reading light in polished brass lacquered housing. Exquisite and innovative design is ideal for any interior lighting applications.*

*Base Dia. 40mm, Lens housing Dia. 25mm and Swivel length 28 mm*

**Material:** Brass  
**Housing Color:** Polished Lacquered Brass  
**LED Quantity:** 1 x 1W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 1.2W  
**Lumen:** 70-80  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00003-BLW  
**Material** Lacquered Brass




## Dimmable LED Swivel Reading Light

*Bright and flexible LED reading light in polished brass lacquered housing. Exquisite and innovative design is ideal for any interior lighting applications. Light comes with a toggle ON/OFF switch.*

*Base Dia. 52mm, Lens housing Dia. 43mm and Swivel length 38 mm*

**Material:** Solid Brass  
**Housing Color:** Polished Lacquered Brass  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00004-BLW  
**Material** Lacquered Brass




## Dimmable LED Swivel Reading

*LED Swivel Reading Light with frosted white glass shade. Light comes with ON/OFF rocker switch. Elegant and innovative design for any reading light application.*

*2.63" L x 3.14" W*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass/ Frosted Glass  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2850-3050K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00926-BLD  
**Material** Lacquered Brass



## Dimmable LED Swivel Reading


*LED Swivel Reading Light with frosted white glass shade. Light comes with ON/OFF rocker switch. Elegant and innovative design for any reading light application.*

*2.63" L x 3.14" W*

**Material:** Brass / Glass Shade  
**Housing Color:** Polished Lacquered Brass/ White Glass  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Wattage:** 3.1W  
**Beam Angle:** 110  
**Color Temperature:** 2900-3200K  
**LED Life Time:** 50000 hrs

**ITEM NO.** P00919-BL  
**Material** Lacquered Brass

# LED Spot Light



## LED Spot Light

LED Spotlight designed with stainless steel bracket for tilting up to 90 degrees and rotatable up to 360 degrees. This light is very powerful and bright. Aluminum alloy housing in black finish provides ample heat sinking to the LEDs to ensure long life operation.

Lamp is waterproofed IP67 rated.

Material: Aluminium Alloy  
Housing Color: Black  
LED Quantity: 5 x 3W  
LED Color: Cool White  
Working Voltage: DC10-30V  
Wattage: 12W  
Beam Angle: 110 degrees  
Lumen: 160  
Color Temperature: 5500 - 6300K  
LED Life Time: 50000 hrs

ITEM NO. LED  
P01612-WB Cool White




## LED High Power Work Light

High power LED work light with chrome plated reflectors for extreme brightness comes pre wired with 2 metres PU Cable for installation. It features versatile single-bolt mounting system. UL 1430, 18AWG light intensity: 9000 Candela. This lamp comes with PC vacuum coated reflector and has stainless steel bracket that allows back & forth tilt adjustment sealed water-tight lens assembly. It has heat sink die casted aluminum and is thermal shock resistant.

Lamp is waterproofed IP67 rated. Operation temperature is -20° to 60° C

Material: Aluminium/PC  
Housing Color: Black  
LED Quantity: 6 x 3W  
LED Color: Cool White  
Working Voltage: 12V DC/11W  
Color Temperature: 5000-6500K  
LED Life Time: 50000hrs

ITEM NO. LED  
P01505-WB Cool White




## LED High Power Spot Light

High power LED spot light with chrome plated reflectors for extreme brightness comes pre wired with 2 metres PU Cable for installation. This lamp comes with stainless steel bracket that allows full the lamp to be fully tilted.

Lamp is waterproofed IP66 rated. Operation temperature is -20° to 60° C

Material: Aluminium/PC  
Housing Color: Black  
LED Quantity: 6 x 3W  
LED Color: Cool White  
Working Voltage: 9-56V DC  
Color Temperature: 5000-6500K  
LED Life Time: 50000hrs

ITEM NO. LED  
P01502-WB Cool White



## LED Spot Light

High power LED spot light with chrome plated reflectors for extreme brightness comes pre wired with 2 metres PU Cable for installation. This lamp comes with stainless steel bracket that allows full the lamp to be fully tilted.

Lamp is waterproofed IP66 rated. Operation temperature is -20° to 60° C. Dimension: 120mm ( Dia. ) x 83.5mm ( Thickness )

Material: Aluminium/PC Outer Ring  
Housing Color: Black  
LED Quantity: 4 x 3W  
LED Color: Cool White  
Working Voltage: 9-56V DC  
Color Temperature: 5000-6500K  
LED Life Time: 50000hrs

ITEM NO. LED  
P01500-WB Cool White

# LED Spot & Underwater Light



## LED High Power Work Light

High power LED work light made of Aluminum Alloy with PC lens. It has convex lens reflector. It comes pre wired with 2 metres PU Cable for installation. This lamp comes with stainless steel bracket that allows full the lamp to be fully tilted.

Lamp is waterproofed IP66 rated. Operation temperature is -20° to 60° C

Material: Aluminium/PC  
Housing Color: Black  
LED Quantity: 8 x 1W  
LED Color: Cool White  
Working Voltage: 13.5 V DC / 0.6 A  
Lux: 39 (3.8 M)  
Color Temperature: 5000-6500K  
LED Life Time: 50000hrs

ITEM NO. LED  
P01506-WB Cool White




## LED High Power Work Light

High power LED work light made of Aluminum Alloy with PC lens. It has convex lens reflector. It comes pre wired with 2 metres PU Cable for installation. This lamp comes with stainless steel bracket that allows full the lamp to be fully tilted.

Lamp is waterproofed IP66 rated. Operation temperature is -20° to 60° C

Material: Aluminium/PC  
Housing Color: Black  
LED Quantity: 24 x 1W  
LED Color: Cool White  
Working Voltage: 13.5 V DC / 1.49 A  
Lux: 107.8 (3.8 M)  
Color Temperature: 5000-6500K  
LED Life Time: 50000hrs

ITEM NO. LED  
P01507-WB Cool White




## Dimmable LED Underwater Light

Surface mount on the transom on the lowest possible location, about 3" above the bottom of the boat. Please make sure the inside of the transom is clear. Lighting unit comes with 1.5M installation PU wire.

Material: Stainless Steel  
LED Quantity: 4 x 3W  
LED Color: WH: Cool White BU: Blue  
Working Voltage: 8-30 V DC  
Wattage: 10.4W  
Beam Angle: 110 degrees  
Lumen: 130-140 x 4  
Color Temperature: Cool White: 5500 - 6400K  
LED Life Time: 50000 hrs

ITEM NO. LED Volt  
P00299-WH Cool White 8-30V  
P00299-BU Blue 8-30V

# LED Reading Light




## Dimmable LED Flexible Chart Light

Flexible LED chart light available in anodized Aluminium housing. This lamp is operated using touch sensor around the housing for easy operation. This lamp is designed so they are always cool, and safe to touch

Material: Aluminium  
Housing Color: Anodized Silver  
LED Color: Warm White  
Working Voltage: 8-30V  
Wattage: 1 x 3W  
Beam Angle: 110 degrees  
Lumen: White: 130-140  
Color Temperature: Warm White: 2850-3200K  
LED Life Time: 50000 hrs

ITEM NO. LED Volt  
P00321-WH Warm White 8-30V

# Ceiling Light



## LED Courtesy/Reading Light

*LED Interior light with rocker switch for ON/OFF operation. 360° Eye Ball Rotating Light.*  
*Size: 115mm L x 77mm W x 48mm H*

**Material:** PC Plastic  
**Housing Color:** Chrome Plated  
**LED Quantity:** 1 x 1W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**Lumen:** 400 Lux at 100cm distance  
**LED Life Time:** 50000 hrs

**ITEM NO.** **LED**  
**P01190-WH** **Warm White LED**




## LED Courtesy/Reading Light

*LED Interior light with rocker switch for ON/OFF operation.*  
*Size: 115mm L x 66.5mm W x 41mm H*

**Material:** PC Plastic  
**Housing Color:** Chrome Plated  
**LED Quantity:** 1 x 3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V DC  
**LED Life Time:** 50000 hrs

**ITEM NO.** **LED**  
**P01191-WH** **1x3W Warm White**




## LED Interior Light

*This LED interior lamp provides warm white light to the interior onboard. This unit does not come with dimming switch.*

**Material:** Plastic w/ Frosted Lens  
**Housing Color:** White  
**LED Quantity:** 1 x 3W  
**LED Color:** Cool White  
**Working Voltage:** 8-30 V DC  
**Wattage:** 3.1W  
**Beam Angle:** 140 degrees  
**Lumen:** White: 130-140  
**Color Temperature:** Cool White: 55000-6300K  
**LED Life Time:** 50000 hrs

**ITEM NO.** **LED** **Switch/Dimmer**  
**P00600-WH** **Warm White** **Without**




## LED Interior Light

*LED Interior Light with ON/OFF rocker switch*  
*6"L x 2 5/8"W x 3/4"H*

**Material:** PC  
**Housing Color:** White  
**LED Quantity:** 5mm x 47  
**LED Color:** White  
**Working Voltage:** 12V

**ITEM NO.** **LED**  
**P01810-12S** **47 x 5mm Cool White LEDs**




## LED Interior Light

*LED Interior Light*  
*6"L x 2 5/8"W x 3/4"H*

**Material:** PC  
**Housing Color:** White  
**LED Quantity:** 5mm x 47  
**LED Color:** White  
**Working Voltage:** 12V

**ITEM NO.** **LED**  
**P01810-12** **47 x 5mm Cool White LEDs**

# Ceiling Light




**LED Ceiling Light**

Energy efficient light made of plastic with Optic Lens. Used for surface mount, it is waterproofed to IP44 rating. It consists of 24 warm white SMD LEDs at 1.7W. ColorTemperature is 2750 - 3250K. It operates in 12V DC. This light is easily installed with screws.

Round Ceiling light measures 65mm diameter.

**ITEM NO.** P09022-W02 **Color** White painting




**LED Ceiling Light**

Energy efficient light made of plastic with Optic Lens. Used for surface mount, it is waterproofed to IP44 rating. It consists of 24 warm white SMD LEDs at 1.7W. ColorTemperature is 2750 - 3250K. It operates in 12V DC. This light is easily installed with screws.

Square Ceiling light measures 65mm by 65mm diameter.

**ITEM NO.** P09023-W02 **Color** White painting




**LED Ceiling Light**

Energy efficient light made of plastic with Optic Lens. Used for surface mount, it is waterproofed to IP44 rating. It consists of 24 warm white SMD LEDs at 1.7W. ColorTemperature is 2750 - 3250K. It operates in 12V DC. Designed as bright slim, it only has 10.2mm of Installation Depth This light is easily installed with clips.

Square Ceiling light measures 70mm by 70mm diameter.

**ITEM NO.** P09025-W05 **Color** Chrome painted




**LED Ceiling Light**

Energy efficient light made of plastic with Optic Lens. Used for surface mount, it is waterproofed to IP44 rating. It consists of 24 warm white SMD LEDs at 1.7W. ColorTemperature is 2750 - 3250K. It operates in 12V DC. This light is easily installed with screws.

Round Ceiling light measures 62.4mm diameter.

**ITEM NO.** P09031-W05 **Color** Chrome Painted



**LED Ceiling Light**


Energy efficient light made of plastic with Optic Lens. Used for surface mount, it is waterproofed to IP44 rating. It consists of 24 warm white SMD LEDs at 1.7W. ColorTemperature is 2750 - 3250K. It operates in 12V DC. This light is easily installed with screws.

Square Ceiling light measures 62.4mm by 62.4 mm

**ITEM NO.** P09032-W05 **Color** Chrome Painted



# LED Ceiling Light




## LED Sensor Light

*LED Light with brightness sensor will only turn on when brightness level is low. Light is ideal for stairways, walkways and lavatories*

Material: Plastic  
Housing Color: White  
LED Quantity: 3 x Top LED  
LED Color: Cool White  
Working Voltage: 12V DC  
Wattage: 0.36W  
Beam Angle: 120 degrees  
Color Temperature: Cool White: 6000K  
LED Life Time: 50000hrs

ITEM NO.	LED	Volt
P00238-WH	Cool White	12V




## LED Motion Sensor Light

*LED Ceiling light in white housing with motion sensor switch and brightness sensor can be mounted on the surface or recessed by detaching the lower rim. This light is ideal for cabin, engine rooms, walkways, and lavatories. Light detects brightness level of the environment and will not turn on when the brightness level is high. Light will turn on when brightness level is low and motion sensor detects movement. Motion sensing distance of approximately 3 metres at 80-90 degrees angle. Light will go off after 40 seconds when no movements are detected.*

Material: PC  
Housing Color: White  
LED Quantity: 1x3W  
LED Color: Cool White  
Beam Angle: 110 degrees  
Lumen: 130-140  
Color Temperature: Cool White: 5500-6300K  
LED Life Time: 50000hrs

ITEM NO.	LED	Volt
P00201-WH	Cool White	8-30V




## LED Slim Bright Ceiling/Courtesy Light

*Recessed mount bright and slim LED light. Slim design of around quarter inch is perfect for installations in minimal spaces. 3.4" Dia. x 0.24" thickness*

Material: Aluminium Alloy  
Housing Color: Silver Plated  
LED Color: WH: Warm White  
CL: White/Red/Green/Blue  
Working Voltage: 8-30V  
Wattage: WH: 3.1W ( Warm White)  
CL: Warm White 0.65W, RGB 0.36W  
Beam Angle: 140 degrees  
Lumen: 130-140  
Color Temperature: Warm White: 2825-3200K  
LED Life Time: 50000 hrs

ITEM NO.	LED	Volt
P00190-WH	1 x 3.1W White	8-30V
P00190-CL	2x0.3W White+ 2xRGB	8-30V




## LED Ceiling Light

*Interior lighting for cabin or compartment, this LED Ceiling light can be mounted on surface or recessed by detaching the lower rim.*

Material: PC  
Housing Color: White  
LED Quantity: 5mm x 12  
LED Color: Warm White  
Working Voltage: 8-30V  
Wattage: 0.87W  
Beam Angle: 15 degrees  
Color Temperature: Warm White: 3200K  
LED Life Time: 50000hrs

ITEM NO.	LED	Volt
P00191-WH	Warm White	8-30V

# LED Ceiling Light




## Bright Slim S.S. LED Ceiling Light

Surface Mount ceiling light in polished stainless steel housing. This unit does not come with a switch. Extra slim design ideal for low headroom installation

Housing Color: Stainless Steel  
 LED Quantity: WH: 16 x Top LED WR: 12 + 4(Red)  
 LED Color: WH: Cool White WR: White + Red  
 Working Voltage: 12V DC  
 Wattage: 1W  
 Beam Angle: 120 degrees  
 Color Temperature: Cool White: 6000K  
 LED Life Time: 50000hrs

ITEM NO.	LED	Lens	Volt
P00601-WH	16xWhite Top	70mm	12V
P00601-WR	12 (White) + 4(Red)	70mm	12V




## Bright Slim S.S. LED Ceiling Light w/ Motion Sensor

Surface mount ceiling light in polished stainless steel with motion sensor switch and brightness sensor. Extra slim design ideal for low headroom installation

Housing Color: Stainless Steel  
 LED Quantity: 16 x Top LEDs  
 LED Color: Cool White  
 Working Voltage: 12V DC  
 Wattage: 1W  
 Beam Angle: 120 degrees  
 Color Temperature: Cool White: 6000K  
 LED Life Time: 50000hrs

ITEM NO.	LED	Lens	Volt
P00601-SWH	16xWhite Top With Sensor	70mm	12V




## Bright Slim S.S. LED Ceiling Light

Surface Mount ceiling light in polished stainless steel housing. This unit does not come with a switch. Extra slim design ideal for low headroom installation

Housing Color: Stainless Steel  
 LED Quantity: 28 x Top LED  
 LED Color: Cool White  
 Working Voltage: 8-30V  
 Wattage: 2.26W  
 Beam Angle: 120 degrees  
 Color Temperature: Cool White: 6000K  
 LED Life Time: 50000hrs

ITEM NO.	LED	Lens
P00602-WH	28 x White Top	100mm




## Bright Slim S.S. LED Ceiling Light w/ Motion Sensor

Surface mount ceiling light in polished stainless steel with motion sensor switch and brightness sensor. Extra slim design ideal for low headroom installation

Housing Color: Stainless Steel  
 LED Quantity: 28 x Top LED  
 LED Color: Cool White  
 Working Voltage: 8-30V  
 Wattage: 2.26W  
 Beam Angle: 120 degrees  
 Color Temperature: Cool White: 6000K  
 LED Life Time: 50000hrs

ITEM NO.	LED	Lens
P00602-SWH	28 x White Top	100mm

# LED Ceiling Light




## Dimmable LED Ceiling Light

*Recessed mount stainless steel LED Ceiling Light with 2 x high powered 3W White and 2 x 0.5W Red LED makes this light extremely bright. Light comes with swivel lens and spring clips*

**Material:** Stainless Steel/Aluminium Alloy  
**Housing Color:** Polished Stainless Steel  
**LED Color:** Cool White + Red  
**Working Voltage:** 8-30V  
**Wattage:** 2x3W (Cool White) + 2x0.5W (Red)  
**Beam Angle:** 110 degrees  
**Lumen:** White 130-140 x 2  
**Color Temperature:** Cool White: 5500-6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED
P01175-CWR	Warm White 6W
P01175-WR	Warm White 6W + Red 1W




## Dimmable LED Ceiling Light

*LED Ceiling Light with 2 high powered 3W White and 2 0.5W Red LED makes this light extremely bright. Light can be mounted on the surface or recessed by detaching the lower rim*

**Material:** Stainless Steel/Aluminium Alloy  
**Housing Color:** Polished Stainless Steel  
**Working Voltage:** 8-30V  
**Wattage:** 2 x 3W(White) + 2 x 0.5W (Red)  
**Beam Angle:** 110 degrees  
**Lumen:** White 130-140 x 2  
**Color Temperature:** Cool White: 5500-6300K  
                                   Warm White: 2850-3200K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED
P01158-CWR	Cool White 6W + Red 1W
P01158-WR	Warm White 6W + Red 1W




## Dimmable LED S.S Ceiling Light

*LED Stainless Steel Ceiling Light with swivel lens and spring clips. LED light is dimmable when connected to dimmer switch.*

**Material:** Aluminium Alloy Base / S.S Rim  
**Housing Color:** Stainless Steel  
**LED Quantity:** 1  
**LED Color:** White  
**Working Voltage:** 8-30V  
**Wattage:** 3.1W  
**Beam Angle:** 110 degrees  
**Color Temperature:** Warm White: 2850-3200K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED
P00458-WH	Warm White 3W



## Dimmable LED Eyeball Light

*LED "Eyeball" Light with swivel lens.*

**Material:** Zinc Alloy  
**Housing Color:** Chrome  
**LED Quantity:** 1x1W  
**LED Color:** Warm White  
**Wattage:** 1.44W  
**Beam Angle:** 110 degrees  
**Lumen:** 77-87  
**Color Temperature:** Warm White: 2850-3200K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00230-WH	Warm White	8-30V




## LED Round High Power Light

*This high power LED light with stainless steel housing is ideal for interior and exterior lighting applications. Light can be flush or surface mounted. Base of the light is made of aluminium and the rim is made of stainless steel. 70.7mm Dia, 46.7mm Lens Dia x 23.6mm H*

**Material:** Aluminium Alloy Base / S.S Rim  
**Housing Color:** Stainless Steel  
**LED Quantity:** 1x3W  
**LED Color:** Warm White  
**Wattage:** 3.1W  
**Beam Angle:** 110 degrees  
**Lumen:** White 140  
**Color Temperature:** Warm White: 2900-3200K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Rim
P00158-SSWH3W	Warm White	S.S.

# LED Dome Light




## LED Dome Light

*Surface mount LED Dome light with on/off switch*

Material: Plastic  
Housing Color: White  
LED Quantity: WH: 16 x 5mm WR: 12 + 4(Red)  
LED Color: WH: Cool White WR: White + Red  
Working Voltage: 12V DC  
Wattage: 1W  
Beam Angle: 120 degrees  
Color Temperature: Cool White: 6000K  
LED Life Time: 50000hrs

ITEM NO.	LED	Volt
P00546-WH	Cool White	12V
P00546-WR	Cool White + Red	12V




## LED Dome Light

*Surface mount LED Dome light with on/off switch. Lamp is made of gold plated ABS plastic. Lens is made of high quality PC plastic.*

Material: Plastic  
Housing Color: Gold Plated  
LED Quantity: 20 x 5mm  
Working Voltage: 12V  
Wattage: 1.7W  
Beam Angle: 15 degrees  
Color Temperature: Warm White: 2850-3200  
LED Life Time: 50000hrs

ITEM NO.	LED	Volt
P00556-WH	Warm White	12V




## LED Ceiling Light

*Surface mount LED ceiling light comes with an ON/OFF toggle switch*

Material: ABS  
Housing Color: Silver  
LED Quantity: 20 x 5mm  
LED Color: Cool White  
Working Voltage: 12/24V DC  
Wattage: 1.3W  
Beam Angle: 15 degrees

ITEM NO.	LED	Volt
P00511-WH	Cool White	12V/24V



## Dimmable LED Dome Light

*High Powered 3W LED Dome light in polished stainless steel finish with high quality plastic lens. Light does not come with ON/OFF switch. New and contemporary design*

Material: S.S Rim/Aluminium Base  
Housing Color: Polished Stainless Steel  
LED Quantity: 1 x 3W  
LED Color: Warm White  
Working Voltage: 8-30V  
Wattage: 3.1W  
Beam Angle: 110  
Lumen: 130-140  
Color Temperature: 2900-3200K  
LED Life Time: 50000hrs

ITEM NO.	LED
P00554-WH	Warm White



# LED Dome Light




## LED Push On/Off Light

*Interior lighting for cabin or compartment, this LED Push On/Off light can be mounted on surface or recessed by detaching the lower rim. The On/Off function is operated by pressing gently on the lens of the lamp.*

**Material:** Plastic (PC) and ABS  
**Housing Color:** White  
**LED Quantity:** 6  
**LED Color:** Cool White  
**Working Voltage:** 12/24V DC  
**Wattage:** 0.443W  
**Beam Angle:** 10 degrees  
**Color Temperature:** 13914K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00075-WHD	Cool White	12V/24V




## LED Round Push ON/OFF Light

*This surface mount LED Courtesy light with white plastic housing is ideal for interior lighting applications. Light comes with a push On/Off switch on the lens. Mounting screws included.*

**Material:** Plastic (PC)  
**Housing Color:** White  
**LED Quantity:** 16  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 1.15W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00165-WH	Cool White	12V
P00164-WH	Cool White	12V




## LED Swivel Light

*Surface mount LED swivel light with ON/OFF toggle switch*

**Material:** ABS  
**Housing Color:** Silver  
**LED Quantity:** 1  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 1.5W  
**Beam Angle:** 120 degrees  
**Color Temperature:** Warm White: 5000-6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00526-SLD	Cool White	12V




## LED Ceiling Light

*LED Ceiling light for recessed/surface mount comes with a press ON/OFF switch on the lens. This lamp is ideal of small cabins and compartments. Installation screws included.*

**Material:** Plastic (PC)  
**Housing Color:** White  
**LED Quantity:** 4 x 5mm  
**LED Color:** Cool White  
**Working Voltage:** 12/24V DC  
**Wattage:** 0.28W  
**Beam Angle:** 45 degrees  
**LED Life Time:** 50000hrs

ITEM NO.	LED	Mount
P00258-WH	Cool White	Flush Only
P00268-WH	Cool White	Surface/Flush

# Courtesy Light




## LED Multi Color Light

Multi colored LED light in polished stainless steel or White Plastic Rim finish for flush mounting. Light comes with high powered 1W white LED and multi colored RGB LEDs around the lens for ambience illumination.

**Material:** Stainless Steel / PC  
**Housing Color:** SSCL: Polished Stainless Steel  
**LED Quantity:** CL: White Plastic  
 1 x 1W High Powered White + 1 x RGB LED  
**LED Color:** Warm White / Red/ Green / Blue  
**Working Voltage:** 8-30V  
**Wattage:** White: 1W Red: 0.06W Blue, Green: 0.09W  
**Beam Angle:** 140 degrees  
**Lumen:** 77-87  
**Color Temperature:** Warm White: 2850-3200K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Rim
P00192-SSCL	Warm White/RGB	S.S.
P00192-CL	Warm White/RGB	White Plastic




## Dimmable Mini Ceiling/Courtesy Light

Recessed Mount mini high power 3W LED ceiling light. Mounting using rubber ring

**Material:** Aluminium Alloy  
**Housing Color:** Anodized Silver  
**LED Quantity:** 1x3W  
**LED Color:** Warm White  
**Working Voltage:** 8-30V  
**Wattage:** 2.76W  
**Beam Angle:** 110 degrees  
**Lumen:** 130-140  
**Color Temperature:** Warm White: 2850-3050K  
**LED Life Time:** 50000hrs

ITEM NO.	LED
P00229-WH3W	Warm White





## Dimmable LED Mini Courtesy Light

Recessed mount mini high powered 1W LED courtesy light with mounting clips

**Material:** Aluminium Alloy  
**Housing Color:** Anodized Silver  
**LED Quantity:** 1x1W  
**LED Color:** Warm White  
**Wattage:** 1.2W  
**Beam Angle:** 110 degrees  
**Lumen:** 70-80  
**Color Temperature:** Warm White: 2850-3050K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED
P00229-WH	Warm White




## LED Round Courtesy Light

This energy efficient and attractive LED light with white plastic housing is ideal for interior and exterior courtesy lighting applications. This light is waterproof. This light can be recessed mounted or surface mounted by attaching plastic lower rim included.

**Material:** PC  
**Housing Color:** White  
**LED Quantity:** 5mm x 3  
**LED Color:** Cool White/Red/Blue  
**Working Voltage:** 12V  
**Wattage:** 0.22W  
**Beam Angle:** 30 degrees  
**Color Temperature:** Cool White: 6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED Color
P00158-WH	Cool White
P00158-RD	Red
P00158-BU	Blue




## LED Round Courtesy Light

This energy efficient and attractive LED light with stainless steel housing is ideal for interior and exterior courtesy lighting applications. Each lamp comes with 3 x 5mm LEDs and waterproof. Recessed mount only

**Material:** Stainless Steel  
**Housing Color:** Polished Stainless Steel  
**LED Quantity:** 5mm x 3  
**LED Color:** SSWH: Cool White  
 SSBH: Blue  
**Working Voltage:** 12V  
**Wattage:** 0.22W  
**Beam Angle:** 30 degrees  
**Color Temperature:** Cool White: 6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED Color
P00158-SSWH	Cool White
P00158-SSBU	Blue




## LED Ceiling/Courtesy Light

This surface mount LED dome/ceiling light offers brightness in small compartments or cabins. Stainless steel mounting screws included. Light comes with ON/OFF toggle switch 3 1/2" W x 1" H

**Material:** Plastic (PC)  
**Housing Color:** White  
**LED Quantity:** 5mm x 3  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.22W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED
P00168-WH	White

# LED Courtesy Light




## LED High Power Square Light

**P00358-SSWH3W:** high powered LED light in square shape is bright and elegant looking with its stainless steel rim. Light is meant for recessed mounting.

**P00358-WH3W:** high powered LED light is made with high quality plastic in square shape housing. Light is meant for surface mounting or recessed mounting when detaching the lower rim.

<b>Material:</b>	<b>SSWH3W:</b> S.S Rim/ Aluminium Base	
	<b>WH3W:</b> White Rim/ Aluminium Base	
<b>LED Quantity:</b>	1x3W	
<b>LED Color:</b>	Warm White	
<b>Wattage:</b>	3.1W	
<b>Beam Angle:</b>	110 degrees	
<b>Lumen:</b>	140	
<b>Color Temperature:</b>	Warm White: 2900-3200K	
<b>LED Life Time:</b>	50000 hrs	

ITEM NO.	LED Color	Volt
P00358-SSWH3W	Warm White	8-30V
P00358-WH3W	Warm White	8-30V




## LED Square Courtesy Light

This energy efficient and attractive LED light with square shaped white plastic housing is ideal for interior and exterior courtesy lighting applications. Each lamp comes with Cool white LEDs and water-proof. This light can be recessed mounted or surface mounted by attaching plastic lower rim included.

<b>Material:</b>	PC Plastic	
<b>Housing Color:</b>	White	
<b>LED Quantity:</b>	3 x 5mm	
<b>LED Color:</b>	Cool White	
<b>Working Voltage:</b>	8-30V DC	
<b>Wattage:</b>	0.22W	
<b>Beam Angle:</b>	30	
<b>Color Temperature:</b>	6300K	
<b>LED Life Time:</b>	50000 hrs	

ITEM NO.	LED Color	Volt
P00358-WH	Cool White	12V




## LED Courtesy Light

LED courtesy light with stainless steel bezel and plastic lens. Recessed mount

<b>Material:</b>	Stainless Steel / Plastic	
<b>Housing Color:</b>	Polished Stainless Steel	
<b>LED Quantity:</b>	5mm x 4	
<b>LED Color:</b>	WH: Cool White RD: Red	
<b>Working Voltage:</b>	12V	
<b>Wattage:</b>	0.38W	
<b>Beam Angle:</b>	30 degrees	
<b>Color Temperature:</b>	6000K	
<b>LED Life Time:</b>	50000 hrs	

ITEM NO.	LED	Volt
P00167-WH	Cool White	12V
P00167-RD	Red	12V




## LED Oblong Courtesy Light

This energy efficient and attractive oblong shape LED courtesy light with stainless steel housing is suitable for interior or exterior courtesy lighting on walkways, step or storage areas. Recessed mount only

<b>Material:</b>	Stainless Steel	
<b>Housing Color:</b>	Polished Stainless Steel	
<b>LED Quantity:</b>	5mm x 2	
<b>LED Color:</b>	SSWH: Cool White SSBU: Blue	
<b>Working Voltage:</b>	12V	
<b>Wattage:</b>	0.21W	
<b>Beam Angle:</b>	30 degrees	
<b>Color Temperature:</b>	6000K	
<b>LED Life Time:</b>	50000 hrs	

ITEM NO.	LED	Volt
P00159-SSWH	Cool White	12V
P00159-SSBU	Blue	12V




## LED Oblong Courtesy Light

This energy efficient and attractive oblong shape LED courtesy light is suitable for interior or exterior courtesy lighting on walkways, step or storage areas. Recessed mount only

<b>Material:</b>	PC	
<b>Housing Color:</b>	Clear	
<b>LED Quantity:</b>	5mm x 2	
<b>LED Color:</b>	WH: White BU: Blue	
<b>Working Voltage:</b>	12V	
<b>Wattage:</b>	0.21W	
<b>Beam Angle:</b>	30 degrees	
<b>Color Temperature:</b>	6000K	
<b>LED Life Time:</b>	50000 hrs	

ITEM NO.	LED	Volt
P00159-WH	Cool White	12V
P00159-BU	Blue	12V

# LED Courtesy Light




## LED Courtesy Light

*LED courtesy light that can be rotated 360 degrees*

Material: ABS  
Housing Color: White  
LED Quantity: 5mm x 8  
LED Color: Cool White  
Working Voltage: 12V  
Wattage: 0.56W  
Beam Angle: 30 degrees  
Color Temperature: 6000K  
LED Life Time: 50000 hrs

ITEM NO.	LED	Volt
P00138-WH	Cool White	12V




## LED Mini Courtesy Light

*Mini LED Courtesy in clear housing ideal for utility lighting in small compartments.*

Material: PC Plastic  
Housing Color: Clear  
LED Quantity: 5mm x 1  
Working Voltage: 12V DC  
Wattage: 0.07W  
Beam Angle: 35  
Color Temperature: WH: 2850-3050K  
CWH: 6000K

ITEM NO.	LED
P00287-WH	Warm White
P00287-CWH	Cool White
P00287-RD	Red
P00287-BU	Blue




## LED Surface Utility Eyeball Light

*This LED eyeball light with 20mm diameter swivel lens provides multi-directional interior lighting for cabin, walkway or compartment. Light can be mounted on the surface.*

Material: ABS  
Housing Color: White  
LED Quantity: 1 x 0.5W  
LED Color: Cool White  
Working Voltage: 8-30V  
Wattage: 0.5W  
Beam Angle: 120 degrees  
Color Temperature: 4500-5500K  
LED Life Time: 50000 hrs

ITEM NO.	LED	Volt
P00137-WH	Cool White	8-30V




## LED Courtesy Light

*This attractive, bright yet energy efficient LED Courtesy light draws less than 0.1A and measures 1 3/4" L x 3 1/4" W.*

Material: PC  
Housing Color: White  
LED Quantity: 5mm x 2  
LED Color: Cool White  
Working Voltage: 12V  
Wattage: 0.23W  
Beam Angle: 30 degrees  
Color Temperature: 6000K

ITEM NO.	LED	Volt
P00160-WH	Cool White	12V



## LED Courtesy Light


*Recessed mount LED Courtesy light*

Material: PC Plastic  
Housing Color: Chrome Plated  
LED Quantity: 5mm x 1  
LED Color: Cool White  
Working Voltage: 12V  
Wattage: 0.21W  
Beam Angle: 30 degrees  
Color Temperature: 6000K

ITEM NO.	LED	Volt
P00189-WH	Cool White	12V



# LED Courtesy Light




## LED Mini Courtesy Light

Mini LED Courtesy Light in plastic white housing for recessed mounting is perfect for lighting installations in minimal spaces.

**Material:** ABS  
**LED Quantity:** P00187-WH: 5mm x 1  
P00188-WH: 5mm x 8  
**LED Color:** Warm White  
**Working Voltage:** 12V  
**Wattage:** P00187-WH: 0.24W  
P00188-WH: 1W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 3200K

ITEM NO.	LED	Qty(5mm)
P00187-WH	Warm White	1
P00188-WH	Warm White	8




## LED Mini Courtesy Light

Mini LED Courtesy Light in chrome plated brass finish for recessed mounting is perfect for lighting installations in minimal spaces.

**Material:** Chrome Plated Brass / PC Plastic  
**Housing Color:** Chrome Plated  
**LED Quantity:** 5mm x 1  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.24W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6000K

ITEM NO.	LED	Volt
P00185-WH	Cool White	12V
P00186-WH	Cool White	12V




## LED Livewell Light

This LED light illuminates your livewell and small utility area. Light is completely sealed and waterproof, energy efficient and bright. Cool white LED bulb draws little energy and emits very little heat. Light Diameter 1 1/2", Thread Diameter 5/8"

**Material:** PC  
**LED Quantity:** 5mm x 1  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.21W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00162-WH	Cool White	12V




## LED Courtesy Light

Surface Mount LED Courtesy light  
3.14" x 0.70" x 0.61"

**Material:** Zinc Alloy  
**Housing Color:** Chrome Plated Zinc  
**LED Quantity:** WH: 5 x Cool White TOP LEDs  
RW: 5xRed "SMD" + 5xWhite "SMD"  
**Working Voltage:** 12V  
**Wattage:** 0.4W  
**Beam Angle:** 110 degrees  
**Color Temperature:** 6300K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00181-WH	5 x Cool White "Top"	12V
P00181-RW	5xRed "SMD" + 5xWhite "SMD"	12V




## LED Courtesy Light

Surface mount LED courtesy light ideal for interior or exterior installations.  
2.8" x 1.5" x 0.4"

**Material:** ABS  
**Housing Color:** White  
**LED Quantity:** 5 x TOP LEDs  
**LED Color:** WH: Cool White  
BU: Blue  
**Working Voltage:** 12V  
**Wattage:** 0.43W  
**Beam Angle:** 120 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00182-WH	Cool White	12V
P00182-BU	Blue	12V

# LED Courtesy Light




## LED Step Down Light

*LED step light made with durable zinc alloy great for stairs, decks or pathways.*

*3 1/4" L x 3/4" W x 1/4" H (thickness)*

**Material:** Zinc Alloy  
**Housing Color:** White  
**LED Quantity:** 4  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.48W  
**Beam Angle:** 110 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00184-WH	Cool White	12V




## LED Rail Light

*LED Courtesy Rail Light can be tilted 180°. Light comes with ON/OFF rocker switch*

**Material:** PC Plastic  
**Housing Color:** White  
**LED Quantity:** 2 x 1W  
**LED Color:** Cool White  
**Working Voltage:** 9-30V  
**Wattage:** 2W  
**Beam Angle:** 40  
**Lumen:** 8.61 Lux  
**Color Temperature:** 17671K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P01171-WH	Cool White	9-30V




## LED Strip Light

*Small utility strip light for flush mount installation feature six cool white LEDs. This light is ideal for lighting the desks, cabin, locker or bilge.*

*5 1/2" x 1.14" x 0.85"*

**Material:** PC Plastic  
**Housing Color:** Clear  
**LED Quantity:** 5mm x 6  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.43W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00183-WH	Cool White	12V




## LED Courtesy Rail Light

*LED Courtesy Rail Light can be tilted 180°. Light comes with ON/OFF rocker switch*  
*173mm L x 30mm W x 30mm H*

**Material:** PC  
**Housing Color:** White  
**LED Quantity:** 5mm x 4  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.3W  
**Beam Angle:** 40 degrees  
**Lumen:** 8.61 Lux  
**Color Temperature:** 17671K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00171-WH	Cool White	12V




## LED Rail Light

*LED Rail Light can be tilted 180°*  
*242mm L x 30mm W x 30mm H*

**Material:** PC Plastic  
**Housing Color:** Silver Plated  
**LED Quantity:** 5mm x 8  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.8W  
**Beam Angle:** 40 degrees  
**Color Temperature:** 5501K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00271-SL	Cool White	12V




## LED Strip Light

*Small utility strip light for surface mount installation feature six cool white LEDs. This light is ideal for lighting the decks, cabin, locker or engine room*

**Material:** PC  
**Housing Color:** Clear  
**LED Quantity:** 5mm x 6  
**LED Color:** Cool White  
**Working Voltage:** 12V  
**Wattage:** 0.43W  
**Beam Angle:** 30 degrees  
**Color Temperature:** 6000K  
**LED Life Time:** 50000 hrs

ITEM NO.	LED	Volt
P00193-WH	Cool White	12V

# LED Bulb




## LED Bulbs" Festoon Type"

**LD00009-WH:** Replaces 42mm x 12 mm point festoon bulbs  
0.5W x 3, 12V

**LD00010-WH:** Replaces 42mm x 12mm point festoon bulbs  
0.5W x 6, 12V

ITEM NO.	LED Q'ty	Wattage	Beam Ang-
PLD00009-WH	3 x 0.5W	1.5W	90
PLD00010-WH	6 x 0.5W	3W	90




## LED Bulbs" Festoon Type"

**PLD00005-WH:** Replaces 30mm x 10 mm point festoon bulbs  
0.55W, 12V

**PLD00006-WH:** Replaces 38mm x 10 mm point festoon bulbs  
0.98W 12V

ITEM NO.	LED Q'ty	Wattage	Beam Angle
PLD00005-WH	1	0.55W	98.4
PLD00006-WH	2	0.98W	135.6




## LED Bulb B15D Type 2.5W High Power

**LED replacement bulb with white LEDs for bayonet B15D**

**LED Quantity:** 10  
**LED Color:** Cool White  
**Wattage:** 1.8W  
**Beam Angle:** 180°  
**Lumen:** 83.71

ITEM NO.	Contact	Pins	Volt
P01162-WHS	Single	Parallel	12V
P01162-WH	Double	Parallel	12V
P01162-WH/1	Double	Non-Parallel	12V
P01162-WH/1+	Double	Non-Parallel	12V
(+/- In The Bottom)			




## LED Bulb B15D Type

**LED replacement bulb with white LEDs for bayonet B15D**

**LED Quantity:** 12 x 5mm  
**LED Color:** Cool White  
**Wattage:** 1W  
**Beam Angle:** 15.3°  
**Lumen:** 41.56

ITEM NO.	Contact	Pins
P00163-WHS	Single	Parallel
P00163-WH	Double	Parallel
P00163-WH/1	Double	Non-Parallel
P00163-WH/1+	Double	Non-Parallel
(+/- In The Bottom)		




## LED Bulb B15D Type

**LED replacement bulb with white LEDs for bayonet B15D**

**LED Quantity:** 9 x 5mm  
**LED Color:** Cool White  
**Wattage:** 0.7W  
**Beam Angle:** 16.4°  
**Lumen:** 8.09

ITEM NO.	Contact	Pins
P00063-WHS	Single	Parallel
P00063-WH	Double	Parallel
P00063-WH/1	Double	Non-Parallel
P00063-WH/1+	Double	Non-Parallel
(+/- In The Bottom)		



## LED Bulb B15D Type

**Single or double Contact and Parallel Pins or non-parallel**

**LED Quantity:** 20 x 5mm  
**LED Color:** Cool White  
**Wattage:** 2.5W  
**Beam Angle:** 30.3°  
**Lumen:** 41.56

ITEM NO.	Contact	Pins
P01163-WHS	Single	Parallel
P01163-WH	Double	Parallel
P01163-WH/1	Double	Non-Parallel
P01163-WH/1+	Double	Non-Parallel
(+/- In The Bottom)		

# LED Bulbs & Strip Light



**LED Bulb G4 Type**

*Side Pin  
23mm Diameter*

LED Quantity: 6 x 0.3W  
LED Color: Warm White  
Working Voltage: 10-30V DC  
Wattage: 1.8W  
Beam Angle: 120  
Lumen: 70  
Color Temperature: 2800-3000K

**ITEM NO.** **Pin**  
**PLD00014-WH** **Side Pin**  
**PLD00014-WH1** **Back Pin**




**LED Bulb G4 Type**

*Side Pin  
28mm Dia.*

LED Quantity: 9 x 0.2W  
LED Color: Warm White  
Working Voltage: 10-30V DC  
Wattage: 1.8W  
Beam Angle: 120  
Lumen: 90  
Color Temperature: 2800-3000K

**ITEM NO.** **Pin**  
**PLD00015-WH** **Side Pin**  
**PLD00015-WH1** **Back Pin**




**LED Bulb G4 Type**

*Side Pins  
31mm Dia.*

LED Quantity: 12 x 0.2W  
LED Color: Warm White  
Working Voltage: 10-30V DC  
Wattage: 2.5W  
Beam Angle: 120  
Lumen: 120  
Color Temperature: 2800-3000K

**ITEM NO.** **Pin**  
**PLD00016-WH** **Side Pin**  
**PLD00016-WH1** **Back Pin**




**Dimmable LED High Power Strip Light**

*LED High Power Strip Light is good for cabinetry or shelf lightings in cabins. Installation screws included*

Material: Aluminium Alloy  
Housing Color: Anodized  
LED Quantity: 6 x 1W  
LED Color: Warm White  
Working Voltage: 12V  
Wattage: 5.76W  
Beam Angle: 110  
Lumen: 77-87 x 6  
Color Temperature: 2850-3050K  
LED Life Time: 50000hrs

**ITEM NO.** **LED**  
**P00245-WH** **Warm White 6 x 1W**



**Dimmable LED High Power Strip Light**

*LED High Power Strip Light is good for cabinetry or shelf lightings in cabins. Installation screws included*

Material: Aluminium Alloy  
Housing Color: Anodized  
LED Quantity: 3 x 1W  
LED Color: Warm White  
Working Voltage: 12V  
Wattage: 2.88W  
Beam Angle: 110  
Lumen: 77-87 x 3  
Color Temperature: 2850-3050K  
LED Life Time: 50000hrs

**ITEM NO.** **LED**  
**P00244-WH** **Warm White 3 x 1W**



# Solar Vent




## Solar Powered Ventilator

Measuring 7 1/2" dia. and 3" H, this water resistant 3" solar powered ventilation comes with a rechargeable battery. Two blades (exhaust and intake) are provided with each vent. It moves up to 700 cu.ft./hr of air during the day on solar power while charging a rechargeable battery to run at night. Ventilation can run on battery for 24 hours at full charge. It is constructed with high impact plastic cover and stainless steel screws are included. No wiring is required during installation and vent comes with a built in on/off switch.

Cutout size 3 3/4"

### ITEM NO.

P13023-BT: Plastic Cover  
P13023-SSBT: S.S. Cover




## Solar Powered Ventilator

Measuring 8 1/2" diameter and 2 3/4" H, this water resistant 4" solar powered ventilation comes with intake & exhaust blades. It moves up to 900 cu.ft./hr of air when powered on solar and with a slight breeze provides passive ventilation at night. It is constructed with durable white plastic (ABS) with stainless steel screws included. Vent comes with a built in on/off switch and no wiring is required.

Cutout size 4 3/4"

### ITEM NO.

P13024




## 4" Solar Powered Ventilator

Measuring 8 1/2" diameter and 4" H, this water resistant 4" solar powered ventilation comes with a rechargeable battery. Two blades (exhaust and intake) are provided with each vent. It moves up to 1100 cu.ft./hr of air during the day on solar power while charging a rechargeable battery to run at night. Ventilation can run on battery for 20 hours at full charge. It is constructed with high impact plastic cover (ABS) and stainless steel screws are included. No wiring is required during installation and vent comes with a built in on/off switch.

Cutout size 4 3/4"

### ITEM NO.

P13028



## 4" Square Solar Power Ventilator


Measuring 9" diameter and 4" H, this water resistant 4" solar powered ventilation comes with a rechargeable battery. Two blades (exhaust and intake) are provided with each vent. It moves up to 1100 cu.ft./hr of air during the day on solar power while charging a rechargeable battery to run at night. Ventilation can run on battery for 20 hours at full charge. It is constructed with high impact plastic cover and stainless steel screws are included. No wiring is required during installation and vent comes with a built in on/off switch. This unit comes with insect screen protector.

Cutout size 4 3/4"

### ITEM NO.

P13029

# Dimmer Switch, Solar Vent




**4" S.S. Solar Powered Ventilator**

Measuring 8 1/2" diameter and 2 3/4" H, this water resistant 4" solar powered ventilation comes with intake & exhaust blades. It moves up to 900 cu.ft./hr of air when powered on solar and with a slight breeze provides passive ventilation at night. It is constructed with stainless steel cover and stainless steel screws are included. No wiring is required during installation.

Cutout size 4 3/4"

**ITEM NO.**  
**P13025**




**4" S.S. Solar Powered Ventilator**

Measuring 8 1/2" diameter and 2 3/4" H, this water resistant 4" solar powered ventilation comes with a rechargeable battery. Two blades (exhaust and intake) are provided with each vent. It moves up to 900 cu.ft./hr of air during the day on solar power while charging a rechargeable battery to run at night. Ventilation can run on battery for 24 hours at full charge. It is constructed with stainless steel cover and stainless steel screws are included. No wiring is required during installation and vent comes with a built in on/off switch.

Cutout size 4 3/4"

**ITEM NO.**  
**P13027**

## Dimmer Switch




**12V Dual Circuit Dimmer Switch w/ Remote Control**

This dual circuit dimmer switch made of high quality PC plastic for interior light dimming function. This dimmer switch comes with a RF remote control. Switch can be controlled via a wall touch panel or remote control. It is designed to control and provide easy remote operation for various LED lighting systems on two independent circuits. The wall touch panel comes with backlight and touch pad sound capability for ease of use. Dimmer switch will turn on to its last operating setting.

Dimmer comes with overload protection. Device will shut off if:

- a) load exceeds 120W
- b) Voltage is <9V or >16V

**ITEM NO.**  
**P01157-WH**



**12V Dimmer Switch**

Dimmer Switch made of high quality PC plastic for interior light dimming function.

Dimmer comes with overload protection. Device will shut off if:

- a) load exceeds 120W
- b) Voltage is <9V or >16V

**ITEM NO.**  
**P01160-WH**

\* P01157WH is the recommended dimmer switch for Pactrade Marine branded high powered dimmable LED Lights. Please check compatibility of other branded high powered LED Lights prior to installation.

# Switch Panel



**3 Gang Splashproof**  
Item #: P10013BK]

3 gang splashproof switch panel made of high quality PC plastic with LED indicators on each switch. 30 preprinted labels included. . This panel can be mounted vertically or horizontally.  
5 1/16" x 4 3/8"  
2x 10A and 1 x 5A circuit breakers with caps. 12 VDC



**3 Gang Splashproof**  
Item #: P10037]

3 gang splashproof switch panel made of black aluminum plate with LED indicators on each switch. Each switch is UL approved. 30 preprinted labels included  
3 3/4" x 5 1/4"  
3 x 15A fuse holders. 12VDC.



**3 Gang Splashproof**  
Item #: P10031BK]

3 gang splashproof switch panel made of black aluminum plate with LED indicators on each switch. Each switch is UL approved. 30 preprinted labels included. This panel can be mounted vertically or horizontally.  
3 3/4" X 5 1/4" 2.5mm thickness  
3 x 15A Circuit breakers with Caps. 12 VDC



**Waterproof Bilge Pump**  
P10299V & P10299H]

Waterproof bilge pump switch panel made of black aluminum plate with UL approved 3-Way Auto-Off-Manual switch. Switch comes with spring return from "Manual" position.  
V: Vertical Panel H: Horizontal panel  
3 1/2" x 2" 12VDC



**6 Gang Splashproof**  
Item #: P10016BK]

6 gang splashproof switch panel made of high quality PC Plastic with LED indicators on each switch. 30 preprinted labels included. This panel can be mounted vertically or horizontally.  
7 1/2" x 5 1/16"  
2 x 15A, 3 x 10A and 1 x 5A circuit breakers with caps. 12V DC



**6 Gang Splashproof**  
Item #: P10067]

6 gang splashproof switch panel made of black aluminum Each switch comes with LED indicator and UL approved. 30 preprinted labels included.  
5 1/4" x 7 1/2"  
6 x 15A fuse holders. 12VDC



**6 Gang Splashproof**  
Item #: P10061BK]

6 gang splashproof switch panel made of aluminum plate. Each switch comes with LED indicator and UL approved. 30 preprinted labels included. This panel can be mounted vertically or horizontally.  
5 1/4" x 7 1/2"  
6 x 15A Circuit breakers with Caps. 12VDC



**8 Gang Splashproof**  
Item #: P10087BK]

8 gang splashproof switch panel made of aluminium plate 2.5mm thick. Each switch comes with LED indicator and UL approved. 30 preprinted labels included. This panel can be mounted vertically or horizontally.  
4 1/2" x 9 3/8"  
8 x 15A circuit breaker with caps. 12VDC



**4 Gang Splashproof**  
Item #: P10047BK

4 gang splashproof switch panel made of black aluminum plate. Each switch comes with LED indicator and UL approved. 30 preprinted labels included.  
3 3/4" x 5 1/4"  
4 x 15A fuse holders, 12VDC



**6 Gang Splashproof**  
Item #: P10068BK]

6 gang splashproof switch panel with cigarette lighter socket made of black aluminium plate. Each switch comes with LED indicator and illuminates when turned on. 25 preprinted square labels included. This panel can be installed vertically or horizontally.  
4" x 8"  
4x15A fuse holder box. 12VDC.



**6 Gang Splashproof**  
Item #: P10063BK

6 gang splashproof switch panel made of black aluminium plate. Each switch comes with LED indicator and illuminates when turned on. 25 preprinted labels included. This panel can be mounted vertically or horizontally.  
4" x 8"  
3x15A fuse box. 12 VDC



**6 Gang w/ Illuminated**  
Item #: P10069

6 gang switch panel made of black aluminium plate. Each switch comes with LED indicator and illuminates when turned on. 20 preprinted labels included.  
6 1/2" x 4 1/2"  
2 x 15A, 2 x 10A and 2 x 5A circuit breakers. 12VDC.

# Switch Panel



**6 Gang Weather Deck Panels**  
Item #: P10156BK

6 gang water resistant deck panel with LED indicators made of high quality ABS. Each switch is UL approved and comes with neoprene cap. This panel comes with 6 x 15A circuit breakers. 30 preprinted labels attached. This panel can be installed vertically or horizontally.  
4 1/4" x 6"  
Multi Volt 8-30V DC



**4 Gang Weather Deck Panels**  
Item #: P10154BK

4 gang water resistant deck panel with LED indicators made of high quality ABS. Each switch is UL approved and comes with neoprene cap. This panel comes with 4 x 15A circuit breakers. 30 preprinted labels attached. This panel can be installed vertically or horizontally.  
4 1/4" x 4 3/8"  
Multi Volt 8-30V DC



**4 Gang Splashproof Switch**  
Item #: P10044

4 gang splashproof switch panel made of UV Stabilized plastic. Each switch is UL approved and comes with neoprene cap. 28 preprintd labels included.  
4 1/4" x 3 3/4"  
2 x 15A fuse box. 12V DC.



**6 Gang Splashproof Switch**  
Item #: P10064

6 gang splashproof switch panel made of UV Stabilized plastic. Each switch is UL approved and comes with neoprene cap. 28 preprintd labels included  
4 1/4" x 4 7/8"  
3 x 15A fuse box. 12 VDC



**6 Gang Splashproof Switch**  
Item #: P10064LT

6 gang splashproof switch panel made of UV Stabilized plastic with LED indicator lights. Each switch is UL approved and comes with neoprene cap. 28 preprinted labels included  
4 1/4" x 4 7/8"  
3 x 15A fuse box. 12VDC



**5 Gang Splashproof Switch**  
Item #: P10160BK

5 gang switch panel with cigarette lighter socket made of UV stabilized plastic. Each switch is UL approved and comes with neoprene cap. 28 preprinted labels included  
4 3/8" x 4 7/8"  
3 x 15A fuse boxes. 12VDC



**Patent**  
US 6775148

**Mini Blade Fuse Holders, w/LED Indicator**

Red LED Indicates When Fuse Is Broken. Clear Insulating Cover Design For Water and Dust Proof. Easy To Open By Pressing The Latch.

Fuse: Mini Blade Fuse  
Input: 100A Max.  
Output: 30A Max. per Circuit  
Base: PBT (UL Flame: 94V-0)  
Cap: PC (UL Flame: 94V-2)  
Terminal: Tin Plated Brass  
Input wire size: #4-6 AWG  
Output wire size: #12-16 AWG  
Torque Rating: 20in-1b (2.25Nm) Max.  
Mounting Torque Rating: 8in-1b (0.9Nm) Max.

ITEM NO.  
P11513-04: 4 Gang  
P11513-06: 6 Gang  
P11513-10: 10 Gang



**Patent**  
US 6775148

**Micro Blade Fuse Holder, w/LED Indicator Lamps**

Red LED Indicates When Fuse Is Broken. Clear Insulating Cover Design For Water and Dust Proof. Easy To Open By Pressing The Latch.

Fuse: Micro Blade Fuse  
Input: 100A Max.  
Output: 30A Max. per Circuit  
Base: PBT (UL Flame: 94V-0)  
Cap: PC (UL Flame: 94V-2)  
Terminal: Tin Plated Brass  
Input wire size: #4-6 AWG  
Output wire size: #12-16 AWG  
Torque Rating: 20in-1b (2.25Nm) Max.  
Mounting Torque Rating: 8in-1b (0.9Nm) Max.

ITEM NO.  
P11512-10: 10 Gang